



This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.



ASSY QTY	ASSY QTY	ASSY QTY	B/O	Part #	UNIT QTY	Description	Material	B/O INFORMATION OR SPECIFICATIONS	Pg.
		X		-103	1	PIVOT ASSY.			2
	X	2		-105		LEG ASSY.			3
X				-107	2	TUBE ASSY.			4
				-113	2	WHEEL BUSHING	STEEL	(INCLUDED WITH -153) MODIFIED	5
				-115	2	HOOK	304 S.S.		6
	1			-117		PLATE	A36/1018/1020 HR		7
	1			-119		LEG TUBE	STEEL	(KOCH METAL SPINNING OR AIRCRAFT HARDWARE, NO HOLES PREFERRED) MODIFIED	8
		1		-121		COLLAR	A36/1018/1020 HR		9
1				-123		PLUG	6061		10
				-127	2	HANDLE	304 S.S.		11
1				-129		INNER TUBE	6061		12
				-131	2	OUTER TUBE	6061		13
				-133	1	WHEEL BLOCK	6061		14
				-134	1	WHEEL BLOCK	6061		15
				-135	2	PIN	303 S.S.		16
			B/O	-137	12	WASHER	STEEL	Ø 1/2 (MCMASTER-CARR #90126A033)	1
			B/O	-139	6	NYLON-INSERT LOCKNUT	STEEL	1/2-20, GRADE 5 (MCMASTER-CARR #95615A220)	1
			B/O	-141	16	WASHER	STEEL	3/8 (MCMASTER-CARR #90108A417)	1
			B/O	-143	8	NYLON-INSERT LOCKNUT	STEEL	3/8-24, GRADE 5 (MCMASTER-CARR #95615A150)	1
			B/O	-145	2	DRIVE SCREW	COATED STEEL	#8 X 1/4 (MCMASTER-CARR #90081A190)	1
			B/O	-147	2	SET SCREW	S.S.	1/4-28 X 3/8 (MCMASTER-CARR #92311A558)	1
			B/O	-149	2	LANYARD	COATED STEEL	Ø1/16 X 8 (CARR LANE #CL-2-C)	NS
			B/O	-150	4	FERRULE	ALUMINUM	Ø1/16 X 3/8 (MCMASTER-CARR #3896T31)	NS
			B/O	-151	2	BALL LOCK PIN	STEEL	(CARR-LANE #CL-8-BLPL-3.5)	1
			B/O	-153	2	CASTER		(GALIFICO #WR9205)	1
			B/O	-155	2	SPRING	S.S.	(LEE SPRING #LC-042G-12-S316)	1
			B/O	-157	8	BOLT	STEEL	3/8-24 X 2-1/2, GRADE 5 (MCMASTER-CARR #91247A227)	1
			B/O	-159	4	BOLT	STEEL	1/2-20 X 4-1/2, GRADE 5 (MCMASTER-CARR #91247A366)	1
			B/O	-161	2	BOLT	STEEL	1/2-20 X 4, GRADE 5 (MCMASTER-CARR #91247A364)	1
			B/O	-165	1	SHIPPING CRATE		(SPECIALTY CRATE "TOW BAR CRATE" (92x14x6.5))	NS
			B/O	-167	2	LANYARD TAB	ALUMINUM	#10 (CARR-LANE #CL-194-TAB-A)	1
			B/O		1	DART PLACARD	ALUMINUM	#RB41011	1
ASSY -107	ASSY -105	ASSY -103							


REVISIONS						
REV	ECR	DESCRIPTION	DATE	INITIAL	APPROVED	
		REDRAWN IN SOLIDWORKS FROM TATTERED ORIGINAL DWG.	2/21/2014	JAG	RW	
1	14-0194	CH'D TITLEBLOCK WAS RED BARN IS DART. <b>-113</b> ADDED DWG. <b>-115</b> CH'D DIM WAS .75 IS (.75). <b>-119</b> ADDED DIM (Ø2.75) S.F. -129. <b>-121</b> CH'D DIMS WAS Ø4.00 IS (Ø4.00). <b>-127</b> CH'D DIM WAS .50 IS (.50). <b>-131</b> B/O INFO WAS 1/2 X 3/4 X 2-5/8 IS 1/2 X 1 X 2-5/8. <b>-131</b> CH'D B/O INFO WAS 3" SCH. 40 X 64 IS 3-1/2" SCH. 40 X 64. <b>-133</b> CH'D DIM WAS 3.50 IS (3.50). CH'D B/O INFO WAS 3-1/2 X 3-5/8 X 13-1/8 IS 3-1/2 X 3-1/2 X 13-1/8. ADDED <b>-134</b> . <b>-135</b> CH'D DIM WAS Ø.380 IS (Ø.380).	10/20/2014	DPD	JAG	
2	15-0026	UPDATED TO NEW DRAFTING STANDARDS. <b>-103</b> ADDED SHIM NOTE. <b>-119</b> CH'D DIM WAS 3.50 IS 3.38. ADDED FULL R TO SLOTT. <b>-123</b> CH'D DIM WAS Ø2.738 IS (Ø2.738) S.F. -129. <b>-133</b> & <b>-134</b> CH'D DIMS WAS 4X R-25 IS 4X R-25. WAS .50 IS 2X .50. WAS 1.500 IS 2X 1.500. WAS 1.2X .50. WAS 1.500 IS 2X 1.500. <b>-137</b> CH'D QTY WAS 6 IS 12. <b>-141</b> CH'D QTY WAS 8 IS 16.	1/30/2015	DPD	JAG	
3	16-0041	UPDATED TO DRAWING STANDARDS. <b>-107</b> ADDED DIMENSIONS 5.25, 1.49-1.50, Ø.515 +.010-.000 THRU ALL. CH'D DIM WAS Ø.500 +.030-.000 THRU ALL IS 2X Ø.500 +.030-.000 THRU ALL. ADDED NOTE <b>△</b> . <b>-113</b> DELETED (.125) ADDED (.50) DIMS. <b>-115</b> CH'D DIMS WAS (.75) IS .75. WAS Ø.404-410 ADDED Ø.400 IS Ø.404-410 Ø.400 S.F. -135. <b>-117</b> CH'D MATERIAL WAS HR P&O IS A36/1018/1020 HR. CH'D DIMS WAS (.25) IS .237-.250. WAS Ø3.00 IS Ø2.99-3.01. <b>-119</b> CH'D CALLOUT WAS FULL R IS FULL R OPTIONAL. CH'D DIMS WAS .25 S.F. -117 IS .2572-.2550. WAS (Ø2.75) S.F. -129 IS Ø2.7457-.27445 S.F. -129. WAS 1.50-1.51. <b>-121</b> CH'D MATL WAS ASTM A513 IS A36/1018/1020 HR. CH'D DIM WAS (Ø4.00) IS Ø4.00. <b>-123</b> CH'D DIM WAS (Ø2.738) S.F. -129 IS Ø2.72-2.75 S.F. -129. <b>-127</b> CH'D DIM WAS (.50) IS .50. WAS Ø.390 THRU IS Ø.404-410 THRU ALL S.F. -135. <b>-129</b> DELETED Ø.500 AND Ø.515 HOLES. MOVED TO -107. ADDED DIMS 3.05 MIN. 6.55 MIN. Ø2.75-2.76 S.F. -119. Ø2.74-2.76 S.F. -123. <b>-131</b> CH'D DIMS WAS (Ø3.068) ENSURE S.F. -129 IS Ø3.122-3.068 S.F. -129 & -133, WAS Ø.092-.096 Ø.22 IS Ø.142-.146 Ø.175. <b>-133</b> & <b>-134</b> CH'D DIM'S WAS 2.38 IS 2.39 +.03-.00. WAS 1.19 IS 1.20. WAS (3.50) IS 3.50. WAS Ø3.060 IS Ø3.059-3.062 S.F. -131. <b>-135</b> CH'D DIM WAS (Ø.380) IS Ø.37-.40 S.F. -115 & -127. <b>-145</b> CH'D B/O REF WAS #90081A077 IS #8 X 1/4 #90081A190. CH'D QTY WAS 6 IS 2. <b>-167</b> ADDED TO BOM.	2/18/2016	RJC	JAG	
4	16-0131	<b>-107</b> REMOVED DIMS 5.25 AND 1.50-1.49. ADDED DIMS 55.50 AND 62.25. <b>-115</b> CH'D DIM WAS Ø.410/404 Ø.400 S.F. -135 IS Ø.410/404 Ø.400 (S.F. -135). <b>-119</b> CH'D DIM WAS Ø2.7457/2.7445 S.F. -129 IS Ø2.7457/2.7445 (S.F. -129). <b>-121</b> CH'D DIM WAS Ø2.960 S.F. -105 IS Ø2.960 (S.F. -105). <b>-123</b> CH'D DIM WAS Ø2.73/2.72 S.F. -129 IS Ø2.73/2.72 (S.F. -129). <b>-127</b> CH'D DIM WAS Ø.410/404 THRU ALL S.F. -135 IS Ø.410/404 THRU ALL (S.F. -135). <b>-129</b> CH'D DIM WAS Ø2.76/2.75 S.F. -119 IS Ø2.76/2.75 (S.F. -119). WAS Ø2.76/2.74 S.F. -123 IS Ø2.76/2.74 (S.F. -123). <b>-133</b> <b>-134</b> CH'D DIM WAS Ø3.062-3.059 S.F. -131 IS (Ø3.062-3.059) S.F. -131.	8/29/2016	DEW	SM	

**NOTES:**  
1. REF: BELL T/N: T101808  
2. COMMERCIALY AVAILABLE EQUIVALENT MATERIAL MAY BE SUBSTITUTED FOR EASE OF MANUFACTURING.

			
TITLE UNIVERSAL HELICOPTER TOW BAR ASSY.			
DWG NO. RB T101808-101			REV 4
MAT'L HEAT TREAT FINISH SPEC		UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES .XXX ± .005 FRACTIONS ± 1/8 .XX ± .01 ANGLES ± 5° .X ± .1 SURFACES = 125/√	
DRAWN BY: CLOUGH		1. BREAK ALL SHARP EDGES .015 X 45° OR .015R	
CHECKED: DUERFELDT		2. DIMENSIONAL LIMITS APPLY AFTER PLATING	
OPQS APPR: ANDERSON		3. INTERPRET DIM AND TOL PER ASME Y14.5M-2009	
QA APPR: LINDSAY		USED ON MODEL	
APPROVED: GILBERT		BELL	
SCALE 1:18	DATE 2/18/2014	SHEET 1 OF 16	

This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.

REVISIONS					
REV	ECR	DESCRIPTION	DATE	INITIAL	APPROVED
2	15-0026	-103 ADDED SHIM NOTE.	1/30/2015	DPD	SM




-103  
PIVOT ASSY

<b>DART AEROSPACE</b>	
TITLE UNIVERSAL HELICOPTER TOW BAR ASSY	
DWG NO. RB T101808-103	REV 4
MAT'L FRT TREAT FINISH POWDER COAT YELLOW	UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES .XXX ± .010 FRACTIONS ± 1/8 .XX ± .03 ANGLES ± 1° .X ± .1 SURFACES = 125°
SPEC FED #13538	1. BREAK ALL SHARP EDGES .015 x 45° OR .015R
DRAWN BY: GILBERT	2. DIMENSIONAL LIMITS APPLY AFTER PLATING
CHECKED: DUERFELDT	3. INTERPRET DIM AND TOL PER ASME Y14.5M-2009
OPPS APPR: ANDERSON	USED ON MODEL
QA APPR: LINDSAY	BELL
APPROVED: GILBERT	
SCALE 1:4	DATE 2/19/2014
SHEET 2 OF 16	

This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.

REVISIONS				
REV	ECR	DESCRIPTION	DATE	INITIAL
				APPROVED



-105


LEG ASSY

<b>DART AEROSPACE</b>	
TITLE UNIVERSAL HELICOPTER TOW BAR ASSY.	
DWG NO. RB T101808-105	REV 4
MAT'L TREAT FINISH SEE -103 SPEC	UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES .XXX ± .010 FRACTIONS ± 1/8 .XX ± .03 ANGLES ± 1° .X ± .1 SURFACES = 125°
DRAWN BY: GILBERT	1. BREAK ALL SHARP EDGES .015 x 45° OR .015R
CHECKED: DUERFELDT	2. DIMENSIONAL LIMITS APPLY AFTER PLATING
OPPS APPR: ANDERSON	3. INTERPRET DIM AND TOL PER ASME Y14.5M-2009
QA APPR: LINDSAY	USED ON MODEL
APPROVED: GILBERT	BELL
SCALE 1:4	DATE 2/18/2014
SHEET 3 OF 16	



This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.

REVISIONS					
REV	ECR	DESCRIPTION	DATE	INITIAL	APPROVED
3	16-0041	-107 ADDED DIMENSIONS 5.25, 1.49-1.50, Ø.515 +.010-.000 THRU ALL, CH'D DIM WAS Ø.500 +.030-.000 THRU ALL IS 2X Ø.500 +.030-.000 THRU ALL. ADDED NOTE 1.	2/18/2016	RJC	JAG
4	16-0131	-107 REMOVED DIMS 5.25 AND 1.50-1.49, ADDED DIMS 55.50 AND 62.25.	8/29/2016	DEW	SM



NOTE:


1 MASK OFF I.D. 3" MIN PRIOR TO POWDER COATING.

(-107)  
TUBE ASSY.

<b>DART AEROSPACE</b>	
TITLE UNIVERSAL HELICOPTER TOW BAR ASSY.	
DWG NO. RB T101808-107	REV 4
MAT'L TREAT FINISH POWDER COAT YELLOW	UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES .XXX ± .010 FRACTIONS ± 1/8 .XX ± .03 ANGLES ± 1° .X ± .1 SURFACES = 125°
SPEC FED #13538	1. BREAK ALL SHARP EDGES .015 x 45° OR .015R
DRAWN BY: CLOUGH	2. DIMENSIONAL LIMITS APPLY AFTER PLATING
CHECKED: DUERFELDT	3. INTERPRET DIM AND TOL PER ASME Y14.5M-2009
OPPS APPR: ANDERSON	USED ON MODEL
QA APPR: LINDSAY	BELL
APPROVED: GILBERT	
SCALE 1:8	DATE 2/18/2014
SHEET 4 OF 16	

This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.

REVISIONS					
REV	ECR	DESCRIPTION	DATE	INITIAL	APPROVED
3	16-0041	-113 DELETED (.125) ADDED (.50) DIMS.	2/18/2016	RJC	JAG



Superseded





(-113)

WHEEL BUSHING

<b>DART AEROSPACE</b>	
TITLE UNIVERSAL HELICOPTER TOW BAR ASSY.	
DWG NO. RB T101808-113	REV 4
MAT'L STEEL	UNLESS OTHERWISE SPECIFIED
HEAT TREAT	DIMENSIONS ARE IN INCHES
FINISH	.XXX ± .010 FRACTIONS ± 1/8
SPEC	.XX ± .03 ANGLES ± 1°
	.X ± .1 SURFACES = 125/✓
DRAWN BY: DUERFELDT	1. BREAK ALL SHARP EDGES
CHECKED: DUERFELDT	.015 x 45° OR .015R
OPPS APPR: ANDERSON	2. DIMENSIONAL LIMITS APPLY
QA APPR: LINDSAY	AFTER PLATING
APPROVED: GILBERT	3. INTERPRET DIM AND TOL PER
	ASME Y14.5M-2009
	USED ON MODEL
	BELL
SCALE 1:1	DATE 10/20/2014
	SHEET 5 OF 16

This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.

REVISIONS					
REV	ECR	DESCRIPTION	DATE	INITIAL	APPROVED
1	14-0194	-115 CH'D DIM WAS .75 IS (.75).	10/20/2014	DPD	JAG
3	16-0041	-115 CH'D DIMS WAS (.75) IS .75, WAS Ø.404-.410 Ψ 4.00 IS Ø.404-.410 Ψ 4.00 S.F. -135.	2/18/2016	RJC	JAG
4	16-0131	-115 CH'D DIM WAS Ø.410/.404 Ψ 4.00 S.F. -135 IS Ø.410/.404 Ψ 4.00 (S.F. -135).	8/29/2016	DEW	SM






(-115)

HOOK

<b>DART AEROSPACE</b>	
TITLE UNIVERSAL HELICOPTER TOW BAR ASSY.	
DWG NO. RB T101808-115	REV 4
MAT'L 304 S.S. HEAT TREAT FINISH SPEC	
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES .XXX ± .010 FRACTIONS ± 1/8 .XX ± .03 ANGLES ± 1° .X ± .1 SURFACES = 125° ✓	
1. BREAK ALL SHARP EDGES .015 x 45° OR .015R 2. DIMENSIONAL LIMITS APPLY AFTER PLATING 3. INTERPRET DIM AND TOL PER ASME Y14.5M-2009	
DRAWN BY: CLOUGH	USED ON MODEL
CHECKED: DUERFELDT	BELL
OPPS APPR: ANDERSON	
QA APPR: LINDSAY	
APPROVED: GILBERT	
SCALE 1:3	DATE 2/18/2014
SHEET 6 OF 16	

This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.

REVISIONS					
REV	ECR	DESCRIPTION	DATE	INITIAL	APPROVED
3	16-0041	-117 CH'D MATERIAL WAS HR P&O IS A36/1018/1020 HR. CH'D DIMS WAS (.25) IS .237-.250, WAS Ø3.00 IS Ø2.99-3.01.	2/18/2016	RJC	JAG







(-117)

PLATE

<b>DART AEROSPACE</b>	
TITLE UNIVERSAL HELICOPTER TOW BAR ASSY.	
DWG NO. RB T101808-117	REV 4
MAT'L A36/1018/1020 HR	UNLESS OTHERWISE SPECIFIED
HEAT TREAT	DIMENSIONS ARE IN INCHES
FINISH SEE -105	.XXX ± .010 FRACTIONS ± 1/8
SPEC	.XX ± .03 ANGLES ± 1°
	.X ± .1 SURFACES = 125° ✓
DRAWN BY: GILBERT	1. BREAK ALL SHARP EDGES
CHECKED: DUERFELDT	.015 x 45° OR .015R
OPPS APPR: ANDERSON	2. DIMENSIONAL LIMITS APPLY
QA APPR: LINDSAY	AFTER PLATING
APPROVED: GILBERT	3. INTERPRET DIM AND TOL PER
	ASME Y14.5M-2009
	USED ON MODEL
	BELL
SCALE 1:4	DATE 2/18/2014
	SHEET 7 OF 16

This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.

REVISIONS					
REV	ECR	DESCRIPTION	DATE	INITIAL	APPROVED
1	14-0194	-119 ADDED DIM (Ø2.75) S.F. -129.	10/20/2014		
2	15-0026	-119 CH'D DIM WAS 3.50 IS 3.38. ADDED FULL R TO SLOT.	1/30/2015	DPD	JAG
3	16-0041	-119 CH'D CALLOUT WAS FULL R IS FULL R OPTIONAL. CH'D DIMS WAS .25 S.F. -117 IS .2572-.2550, WAS (Ø2.75) S.F. -129 IS Ø2.7457-2.7445 S.F. -129, WAS 1.50 IS 1.50-1.51.	2/18/2016	RJC	JAG
4	16-0131	-119 CH'D DIM WAS Ø2.7457/2.7445 S.F. -129 IS Ø2.7457/2.7445 (S.F. -129).	8/29/2016	DEW	SM



(-119)



LEG TUBE

<b>DART AEROSPACE</b>	
TITLE UNIVERSAL HELICOPTER TOW BAR ASSY.	
DWG NO. RB T101808-119	REV 4
MAT'L STEEL	UNLESS OTHERWISE SPECIFIED
HEAT TREAT	DIMENSIONS ARE IN INCHES
FINISH SEE -105	.XXX ± .010 FRACTIONS ± 1/8
SPEC	.XX ± .03 ANGLES ± 1°
	.X ± .1 SURFACES = 125°
DRAWN BY: GILBERT	1. BREAK ALL SHARP EDGES
CHECKED: DUERFELDT	.015 x 45° OR .015R
OPPS APPR: ANDERSON	2. DIMENSIONAL LIMITS APPLY
QA APPR: LINDSAY	AFTER PLATING
APPROVED: GILBERT	3. INTERPRET DIM AND TOL PER
	ASME Y14.5M-2009
	USED ON MODEL
	BELL
SCALE 1:2	DATE 2/18/2014
	SHEET 8 OF 16



This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.

REVISIONS					
REV	ECR	DESCRIPTION	DATE	INITIAL	APPROVED
1	14-0194	-121 CH'D DIMS WAS Ø4.00 IS (Ø4.00).	10/20/2014	DPD	JAG
3	16-0041	-121 CH'D MAT'L WAS ASTM A513 IS A36/1018/1020 HR. CH'D DIM WAS (Ø4.00) IS 4.00.	2/18/2016	RJC	JAG
4	16-0131	-121 CH'D DIM WAS Ø2.960 S.F. -105 IS Ø2.960 (S.F. -105).	8/29/2016	DEW	SM




(-121)

COLLAR

<b>DART AEROSPACE</b>	
TITLE UNIVERSAL HELICOPTER TOW BAR ASSY.	
DWG NO. RB T101808-121	REV 4
MAT'L A36/1018/1020 HR	UNLESS OTHERWISE SPECIFIED
HEAT TREAT	DIMENSIONS ARE IN INCHES
FINISH SEE -103	.XXX ± .010 FRACTIONS ± 1/8
SPEC	.XX ± .03 ANGLES ± 1°
	.X ± .1 SURFACES = 125
DRAWN BY: CLOUGH	1. BREAK ALL SHARP EDGES
CHECKED: DUERFELDT	.015 x 45° OR .015R
OPPS APPR: ANDERSON	2. DIMENSIONAL LIMITS APPLY
QA APPR: LINDSAY	AFTER PLATING
APPROVED: GILBERT	3. INTERPRET DIM AND TOL PER
	ASME Y14.5M-2009
	USED ON MODEL
	BELL
SCALE 1:2	DATE 2/18/2014
	SHEET 9 OF 16



This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.

REVISIONS					
REV	ECR	DESCRIPTION	DATE	INITIAL	APPROVED
2	15-0026	-123 CH'D DIM WAS Ø2.738 IS (Ø2.738) S.F. -129.	1/30/2015	DPD	JAG
3	16-0041	-123 CH'D DIM WAS (Ø2.738) S.F. -129 IS Ø2.72-2.73 S.F. -129.	2/18/2016	RJC	JAG
4	16-0131	-123 CH'D DIM WAS Ø2.73/2.72 S.F. -129 IS Ø2.73/2.72 (S.F. -129).	8/29/2016	DEW	SM



Ø 2.73  
Ø 2.72  
(S.F. -129)

CENTERS OK




(-123)

PLUG

<b>DART</b> AEROSPACE	
TITLE UNIVERSAL HELICOPTER TOW BAR ASSY.	
DWG NO. RB T101808-123	REV 4
MAT'L 6061	UNLESS OTHERWISE SPECIFIED
HEAT TREAT	DIMENSIONS ARE IN INCHES
FINISH SEE -107	.XXX ± .010 FRACTIONS ± 1/8
SPEC	.XX ± .03 ANGLES ± 1°
	.X ± .1 SURFACES = 125
DRAWN BY: GILBERT	1. BREAK ALL SHARP EDGES
CHECKED: DUERFELDT	.015 x 45° OR .015R
OPPS APPR: ANDERSON	2. DIMENSIONAL LIMITS APPLY
QA APPR: LINDSAY	AFTER PLATING
APPROVED: GILBERT	3. INTERPRET DIM AND TOL PER
	ASME Y14.5M-2009
SCALE 1:2	DATE 2/18/2014
	SHEET 10 OF 16

This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.

REVISIONS					
REV	ECR	DESCRIPTION	DATE	INITIAL	APPROVED
1	14-0194	-127 CH'D DIM WAS .50 IS (.50).	10/20/2014	DPD	JAG
3	16-0041	-127 CH'D DIM WAS (.50) IS .50, WAS Ø.390 THRU IS Ø.404-.410 THRU ALL S.F. -135.	2/18/2016	RJC	JAG
4	16-0131	-127 CH'D DIM WAS Ø.410/.404 THRU ALL S.F. -135 IS Ø.410/.404 THRU ALL (S.F. -135).	8/29/2016	DEW	SM




-127

HANDLE

<b>DART AEROSPACE</b>	
TITLE UNIVERSAL HELICOPTER TOW BAR ASSY.	
DWG NO. RB T101808-127	REV 4
MAT'L 304 S.S.	UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES
HEAT TREAT	.XXX ± .010 FRACTIONS ± 1/8
FINISH	.XX ± .03 ANGLES ± 1°
SPEC	.X ± .1 SURFACES = 125° ✓
DRAWN BY: CLOUGH	1. BREAK ALL SHARP EDGES .015 x 45° OR .015R
CHECKED: DUERFELDT	2. DIMENSIONAL LIMITS APPLY AFTER PLATING
OPPS APPR: ANDERSON	3. INTERPRET DIM AND TOL PER ASME Y14.5M-2009
QA APPR: LINDSAY	USED ON MODEL
APPROVED: GILBERT	BELL
SCALE 1:1	DATE 2/18/2014
SHEET 11 OF 16	

This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.

REVISIONS					
REV	ECR	DESCRIPTION	DATE	INITIAL	APPROVED
3	16-0041	-129 DELETED Ø.500 AND Ø.515 HOLES, MOVED TO -107. ADDED DIMS 3.05 MIN, 6.55 MIN, Ø2.75-2.76 S.F. -119, Ø2.74-2.76 S.F. -123.	2/18/2016	RJC	JAG
4	16-0131	-129 CH'D DIM WAS Ø2.76/2.75 S.F. -119 IS Ø2.76/2.75 (S.F. -119), WAS Ø2.76/2.74 S.F. -123 IS Ø2.76/2.74 (S.F. -123).	8/29/2016	DEW	SM



SECTION A-A

-129



INNER TUBE

<b>DART AEROSPACE</b>	
TITLE UNIVERSAL HELICOPTER TOW BAR ASSY.	
DWG NO. RB T101808-129	REV 4
MAT'L 6061	UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES
HEAT TREAT	.XXX ± .010 FRACTIONS ± 1/8
FINISH SEE -107	.XX ± .03 ANGLES ± 1°
SPEC	.X ± .1 SURFACES = 125°
DRAWN BY: GILBERT	1. BREAK ALL SHARP EDGES .015 x 45° OR .015R
CHECKED: DUERFELDT	2. DIMENSIONAL LIMITS APPLY AFTER PLATING
OPPS APPR: ANDERSON	3. INTERPRET DIM AND TOL PER ASME Y14.5M-2009
QA APPR: LINDSAY	USED ON MODEL
APPROVED: GILBERT	BELL
SCALE 1:3	DATE 2/18/2014
SHEET 12 OF 16	



This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.

REVISIONS					
REV	ECR	DESCRIPTION	DATE	INITIAL	APPROVED
3	16-0041	-131 CH'D DIMS WAS (Ø3.068) ENSURE S.F. -129 IS Ø3.122 -3.068 S.F. -129 & -133, WAS Ø.092-.096 ↓.22 IS Ø.142-.146 ↓ 1.75.	2/18/2016	RJC	JAG






(-131)

OUTER TUBE

<b>DART AEROSPACE</b>	
TITLE UNIVERSAL HELICOPTER TOW BAR ASSY.	
DWG NO. RB T101808-131	REV 4
MAT'L 6061	UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES
HEAT TREAT	.XXX ± .010 FRACTIONS ± 1/8
FINISH POWDER COAT YELLOW	.XX ± .03 ANGLES ± 1°
SPEC FED #13538	.X ± .1 SURFACES = 125/✓
DRAWN BY: GILBERT	1. BREAK ALL SHARP EDGES .015 x 45° OR .015R
CHECKED: DUERFELDT	2. DIMENSIONAL LIMITS APPLY AFTER PLATING
OPPS APPR: ANDERSON	3. INTERPRET DIM AND TOL PER ASME Y14.5M-2009
QA APPR: LINDSAY	USED ON MODEL
APPROVED: GILBERT	BELL
SCALE 1:3	DATE 2/18/2014
SHEET 13 OF 16	

This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.

REVISIONS					
REV	ECR	DESCRIPTION	DATE	INITIAL	APPROVED
1	14-0194	-133 CH'D DIM WAS 3.50 IS (3.50).	10/20/2014	DPD	JAG
2	15-0026	-133 CH'D DIMS WAS 4X R.25 IS 4X R.38, WAS .50 IS 2X .50, WAS 1.500 IS 2X 1.500, WAS .50 IS 2X .50, WAS 1.500 IS 2X 1.500.	1/30/2015	DPD	JAG
3	16-0041	-133 CH'D DIM'S WAS 2.38 IS 2.39 +03-.00, WAS 1.19 IS 1.20, WAS (3.50) IS 3.50, WAS Ø3.060 IS Ø3.059-3.062 S.F. -131.	2/18/2016	RJC	JAG
4	16-0131	-133 CH'D DIM WAS Ø3.062-3.059 S.F. -131 IS (Ø3.062-3.059) S.F. -131.	8/29/2016	DEW	SM





(-133)

WHEEL BLOCK

<b>DART AEROSPACE</b>	
TITLE <b>UNIVERSAL HELICOPTER TOW BAR ASSY.</b>	
DWG NO. <b>RB T101808-133</b>	REV <b>4</b>
MAT'L 6061 HEAT TREAT FINISH POWDER COAT YELLOW SPEC FED #13538	
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES .XXX ± .010 FRACTIONS ± 1/8 .XX ± .03 ANGLES ± 1° .X ± .1 SURFACES = 125°	
1. BREAK ALL SHARP EDGES .015 x 45° OR .015R 2. DIMENSIONAL LIMITS APPLY AFTER PLATING 3. INTERPRET DIM AND TOL PER ASME Y14.5M-2009	
DRAWN BY: CLOUGH	USED ON MODEL
CHECKED: DUERFELDT	BELL
OPPS APPR: ANDERSON	
QA APPR: LINDSAY	
APPROVED: GILBERT	
SCALE 1:4	DATE 2/18/2014
SHEET 14 OF 16	


REVISIONS					
REV	ECR	DESCRIPTION	DATE	INITIAL	APPROVED
2	15-0026	-134 CH'D DIMS WAS 4X R.25 IS 4X R.38, WAS .50 IS 2X .50, WAS 1.500 IS 2X 1.500, WAS .50 IS 2X .50, WAS 1.500 IS 2X 1.500.	1/30/2015	DPD	JAG
3	16-0041	-134 CH'D DIM'S WAS 2.38 IS 2.39 +03-.00, WAS 1.19 IS 1.20, WAS {3.50} IS 3.50, WAS Ø3.060 IS Ø3.059-3.062 S.F. -131.	2/18/2016	RJC	JAG
4	16-0131	-134 CH'D DIM WAS Ø 3.062-3.059 S.F. -131 IS {Ø 3.062-3.059} S.F. -131.	8/29/2016	DEW	JAG



			
TITLE UNIVERSAL HELICOPTER TOW BAR ASSY.			
DWG NO. RB T101808-134			REV 4
MAT'L 6061		UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES	
HEAT TREAT		.XXX ± .010 FRACTIONS ± 1/8	
FINISH POWDER COAT YELLOW		.XX ± .03 ANGLES ± 1°	
SPEC FED #13538		.X ± .1 SURFACES = 125/√	
DRAWN BY: CLOUGH		1. BREAK ALL SHARP EDGES .015 x 45° OR .015R	
CHECKED: DUERFELDT		2. DIMENSIONAL LIMITS APPLY AFTER PLATING	
OPSS APPR: ANDERSON		3. INTERPRET DIM AND TOL PER ASME Y14.5M-2009	
QA APPR: LINDSAY		USED ON MODEL	
APPROVED: GILBERT		BELL	
SCALE 1:4	DATE 2/18/2014	SHEET 15 OF 16	

This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.

REVISIONS					
REV	ECR	DESCRIPTION	DATE	INITIAL	APPROVED
1	14-0194	-135 CH'D DIM WAS Ø.380 IS (Ø.380).	10/20/2014	DPD	JAG
3	16-0041	-135 CH'D DIM WAS (Ø.380) IS Ø.37-.40 S.F. -115 & -127.	2/18/2016	RJC	JAG



(-135)  
PIN

<b>DART AEROSPACE</b>	
TITLE UNIVERSAL HELICOPTER TOW BAR ASSY.	
DWG NO. RB T101808-135	REV 4
MAT'L 303 S.S.	UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES
HEAT TREAT	.XXX ± .010 FRACTIONS ± 1/8
FINISH	.XX ± .03 ANGLES ± 1°
SPEC	.X ± .1 SURFACES = 125/✓
DRAWN BY: CLOUGH	1. BREAK ALL SHARP EDGES .015 x 45° OR .015R
CHECKED: DUERFELDT	2. DIMENSIONAL LIMITS APPLY AFTER PLATING
OPPS APPR: ANDERSON	3. INTERPRET DIM AND TOL PER ASME Y14.5M-2009
QA APPR: LINDSAY	USED ON MODEL
APPROVED: GILBERT	BELL
SCALE 1:1	DATE 2/18/2014
SHEET 16 OF 16	